

AIR SAFE ... Why Bounce When You Can Glide.

3 for the price of 1



AIRBOX™ #18018

Simply increase or decrease air pressure in the revolutionary AIRBOX and go from a 15K to an 18K... in seconds!



AIRBOX™ with Slider #18828
Perfect for short box pickups.

Adjustability • Flexibility • Reliability

The AIRBOX Revolution is the most versatile and compact 15K, 16K and 18K Air Hitch system ever designed. Its economically priced and AIRSAFE™ tough. Whether you have a long box or short box and need a regular rail base, slider, or underbed system, the AIRBOX Revolution is your ticket to a First-Class ride at the price of coach. By placing two commercial grade air bags directly below the hitch head it allows us to make a compact air hitch that virtually absorbs trailer to AIRBOX™ forces. Its tough, but light-weight design allows you to quickly and easily remove it from your bed when not needed and quickly re-attach when needed. If you have ever been wondering if an Air Hitch system is for you, here is your answer. You and your passenger deserve the very best.



AIRBOX head floats on 2 heavy-duty air bags giving you the industry's finest ride.

Part #	Rating	Pin Wt.	G.T.W.W.	Description
18018	3 in 1 15K, 16K, 18K	4,000 lb.	18,000 lbs.	AIRBOX
18828	3 in 1 15K, 16K, 18K	4,000 lb.	18,000 lbs.	AIRBOX w/slider

(Mounting hardware not included)



AIR SAFE™

Upgrade Your Current 15K, 16K, or 18K Fifth Wheel Hitch, into a First Class Air System.

You're almost there. You want a world-class air ride system, but have already spent money on the traditional 5th wheel. You're in luck... save money by simply using your existing REESE, HUSKY, VALLEY, or RBW 15K, 16K, or 18K head, towers, and rails. Now remove your existing 5th wheel crossmember, and replace it with the AIRSAFE AIRBOX. It's that easy! Look below and find your AIRBOX™ Air Ride upgrade. Installation is simple, the ride is unbelievable, and your quality of life improved.

Part #	AIRBOX Upgrade*
24150	15K Reese Pro Series
24762	15K Reese
24161	16K Reese
24150	15K Husky/Valley
16160	16K Husky/Valley
24153	15K RBW LII® Rocker
24163	16K RBW X16

*Upgrade includes application-specific AIRBOX with hardware



Head, Tower and Rails Not Included

AIR SAFE OMNI DIRECTIONAL 5TH WHEEL HITCHES

Heavy-Duty AIR SAFE Air Hitch Systems.



Fill all four air bags from one point
Adjustable flow control valves allow for user specific ride control
Maintenance-Free

25K Binkley commercial head with 1 1/4" locking jaws
Adjustable head height 14-21"

AIRSAFE™ Air Hitches with its multi-directional movement delivers smooth motion adjusting to surge, bucking, twisting and trailer sway. Specifically engineered for today's larger tow vehicles and trailers.

Four exclusive tapered Air Springs absorb 90% of road shock resulting in a smooth, safe ride.



- Reduces Driver Fatigue
- Increases Ride Quality
- Improves Overall Safety
- Increases Life of Transmission
- Increases Tire Life
- Increases Life of Trailer
- Increases Life of Electronics

Part #	Rating	Pin Wt.	G.T.W.W.	Description
22020	20K	5,500 lb.	20,000 lbs.	AIRSAFE Omni-Directional
25027	25K	5,500 lb.	25,000 lbs.	AIRSAFE Omni-Directional

(Mounting hardware not included)

AIR SAFE

Upgrade your REESE, VALLEY, RBW, or HUSKY 20K, 22K, 24K, & 25K Hitch.

Why toss away your current head and rails when you can simply attach them to our AIRSAFE™ towers and custom yoke. Find your application for the AIRSAFE™ upgrade system, order it today, and you will save money and increase your quality of ride.


Part #	Tower Upgrade*
255702	Towers for Upgrade
Part #	Yoke Upgrade*
280034	18K Reese Select
280033	20K Reese Yoke
280034	22K Reese Yoke
287067	24K Husky/Valley Yoke
287075	25K Husky/Valley Yoke
280022	22K RBW Yoke
287072	20K Husky/Valley Yoke

*All upgrades require tower #255702 plus the yoke specific application



Reese Upgraded
Valley Upgraded

COMMERCIAL GRADE AIRSAFE FIFTH WHEEL



32K AIRSAFE AIR RIDE SYSTEM
6,000 lb. pin weight
32,000 GVW
5/8" steel plate

Binkley/Holland 32K Head

Works on Class 7 & 8 conversions

The 32K AIRSAFE™ 5th Wheel Hitch is designed for Medium Duty Trucks and Class 8 conversions. Featuring the Binkley/Holland head with full 1 1/4" thick jaws, this unit is made to handle the big jobs. 6,000 lb. pin weight and 32,000 GVW. Two custom heavy-duty air springs make it the tower of choice.

Part #	Description
32007	32K



AIR SAFE RECEIVER HITCHES

Custom, steel tie-rods for maximum force transfer, ensuring life-long durability. Virtually maintenance free.

Designed • Engineered • Manufactured by the foremost supplier of performance tie rods

Industrial air bag to reduce shock by 90%, giving you the smoothest ride possible.

AIRSAFE Class III

AIRSAFE Class IV

AIRSAFE Class V

AIRSAFE Class VI

AIRSAFE Class VII

AIRSAFE Class VIII

Accessories for above Receiver Hitches

1/2" Plate Ball Mount
(must be used with 05000 & 06000)
#06285

12" Weight Distribution Bracket
#06901

16" Weight Distribution Bracket
#06909

3/4" Plate HD Ball Mount
(must be used with 07000 & 08000)
#06709

Extended Ball Mount
#06609

Part #	AIRSAFE	T.W.	G.V.W.	Shank
04001	Class IV	1,000 lbs.	10,000 lbs.	2" x 6.5"
05000	Class V	1,400 lbs.	14,000 lbs.	2" x 11"
05085	Class V	1,400 lbs.	14,000 lbs.	2" x 8.5"
06000	Class VI	2,000 lbs.	20,000 lbs.	2" x 6.5"
06085	Class VI	2,000 lbs.	20,000 lbs.	2" x 8.5"
26120	Class VI*	2,000 lbs.	20,000 lbs.	2" x 8.5"
26125	Class VI*	2,500 lbs.	25,000 lbs.	2" x 14.5"
07000	Class VII	2,500 lbs.	25,000 lbs.	2.5" x 6.5"
08000	Class VII	3,000 lbs.	30,000 lbs.	2.5" x 6.5"
08085	Class VII*	3,000 lbs.	30,000 lbs.	2.5" x 8.5"
28100	Class VIII*	3,000 lbs.	30,000 lbs.	2.5" x 12.5"
28120	Class VIII*	2,500 lbs.	25,000 lbs.	2.5" x 14.5"

Part #	Accessory/Description
06444	Adjustable Hitch Plate for Class III & IV
06901	12" Weight Distribution Bracket
06285	Ball Mount Bracket for Class V & VI
06709	HD Ball Mount Bracket Class VII & VIII



AIR SAFE AIR GOOSENECKS NEW!

Protect Your Precious Cargo.

AIRSAFE GOOSENECKS
7,000 lb. Pin Weight
26,000 lb. GTW

Available in round or square tube

Internal nylon composite allows smooth sliding motion

Simply connects to existing trailer pin

Easy access to air valve

Heavy-duty Air Shocks reduce oscillation

36,000 lb. rating on steel couplers, machined from solid stock steel

8" diameter industrial air springs for maximum shock absorption

1" and 2" spacer rings for proper ride height

AIRSAFE™ goosenecks are engineered with you and your precious cargo's comfort and safety in mind.

Our exclusive design protects cargo from injury by nearly eliminating shock transferred from the vehicle to the trailer. Our goal is for you and your cargo to "Arrive alive and enjoy the drive". Veterinarian approved and construction industry tough. Prevent vehicle damage and increase your gas mileage. What a great way to save your hard earned money.

- Reduces trailer and content fatigue
- Reduces driver fatigue
- Increase gas mileage
- Your animals will love you
- Increase tire and trailer life

Part #	Description
50100R	Gooseneck, Round Tube
50100S	Gooseneck, Square Tube

The Facts. AirSafe Receivers, Fifth Wheels & Goosenecks.

Safety
With Air Hitches only 10% of the trailer inertia transfers compared to 100% using a hard connection hitch giving you ultimate control. Reduces driver fatigue to help ensure everyone (family, friends, pets, horses, and livestock) arrives alive.

Ultimate Control

- The tow vehicle and trailer track independently giving you greater control and added safety, virtually eliminating all sway.
- Greatly increased braking control since all the weight on the tow vehicle and trailer is distributed evenly giving you increased positive contact when breaking and maneuvering.

Safeguards Against Uncontrollable Road Conditions
Bumps, potholes, expansion joints, curves, hills, and other drivers can be a hazard, keeps you under control when confronted with these conditions.

Saves You Money
Reduces trailer and content fatigue. Metal fatigue caused by traditional towing results in your trailer and its contents taking a beating. Products increase life and help hold value.



800-457-1242